

PLANNING BOARD TOWNSHIP OF MARLBORO

VARIANCE APPLICATION

1. Identification of all sections of zoning ordinance from which relief is sought.

220-90E(1)	- Min. parking lot setback from street line is 80 feet. Proposed is 47.7 feet.
220-97B	- Off-street parking space is 10'x20'. Proposed parking spaces are 9'x20'.
220-97C(6)	- No parking shall be within 30' of structure. Proposed parking is 10' from structure.
220-97F(11)	- Total of 101 parking spaces are required for Phase I & 137 parking spaces for total phase I & II.
	Total of 80 parking spaces are proposed for both phases.
220-35D(24)(E)	- Max. slope for lawn is 10% (5' from building) & 25% beyond. Max. slope proposed is 33%.
337-23A(2)	 Foundation plantings are required on all sides of building. There are no landscaping on the south and west sides of the building.
337-23A(4)	 One shade tree shall be planted for every five (5) parking space; 14 are required. Ten (10) trees are proposed within the parking lot.

2. Statement of reasons why variances are needed

2. Statement of feasons why variances are needed		
220-90E(1)	- Due to NJDEP buffer constraints, development shifts closer to property line.	
`220-97B	 9'x18' parking space is a common industry standard and is typical in most Townships. Project proposes 9'x20'. 	
220-97C(6)		
• ,	 Due to NJDEP buffer constraints, development shifts closer to property line. 	
220-97F(11)	 84 parking spaces is excessive. 70 parking spaces is more than adequate for the proposed use. 	
220-35D(24)(E	common industry standard and is acceptable in most Township and Soil Conservation Districts.	
	The site will be stabilized in accordance with FSCD standards.	
337-23A(2)	 Possibility of building expansion may be proposed on the south side of the building. West side of the building consists of riprap and splash block. 	
337-23A(4)	- Lawn area within the parking lot consists of swales, pipes and inlets to comply with	
(1)	stormwater quantity requirement. The area has limited space for trees	